

**baby lock**

## Double Fold Bias Binder

1-1/8 inch (28mm) Item No: B0421S03A-E (BLE8-S3)

1-1/2 inch (36mm) Item No: B0421S02A-E (BLE8-S2)

For 1-1/2 inch Binder:

**Stitches Used:**

**Chain Stitch - C3 Needle Position**

**Narrow Right Cover Stitch C2-C3**

**Type of Application: Binding the edge of projects. Sewing Speed: Slow to moderate**

**Fabrics Used: Lightweight to medium weight woven fabrics cut on Bias.**

For 1-1/8 inch Binder:

**Stitches Used:**

**Narrow Right Cover Stitch C2-C3**

**Chain Stitch - C3 Needle Position**

**INSTRUCTIONS:**

**Stitch Length: 3-4**

**Upper Knife: Disengaged "LOCKED"**

**Upper Looper: Down**

**Sewing Table: On**

**Bias Strip Cut Size:**

1-1/8 inch Binder: Cut 1-1/8 inch bias from fine fabrics such as calico, muslin, etc.  
Cut 1 inch wide for medium weight fabrics such as trigger, lt. wt. denim.

1-1/2 inch Binder: Cut 1-3/8 inch for fine fabrics such as calico, muslin, etc.  
Cut 1-1/4 inch wide for medium weight fabrics such as trigger, lt. wt. denim.

Test with fabric strip to make sure of correct width of bias.

1. Secure attachment to table with guide fixing screws.
2. Cut fabric strips to size needed.
3. Raise presser foot. With the point of the bias strip, place strip into attachment. Use tweezers to feed the strip into the attachment.
4. Place the folded bias up to the needles and under the presser foot.
5. Turn the hand wheel 3-4 times to secure the stitching in the fabric.
6. Place the fabric that is to be bound into the slot of the attachment. Place in the folded bias in front of the presser foot.
7. Loosen the guide fixing screws and move the attachment right or left to align the attachment with the needle position.
8. Sew test for proper alignment before sewing on project.

