



<b>Available for:</b>
BLETS8, BLETS8AE, BLES8, BLES8W-2, BLE5-3, BLCS

# Belt Loop Folder

Item No: B0421S12A 3/4 inch (19mm)

Item No: B0421S11A 1-1/2 inch (38mm)

**Type of Application:**

Making belt loops for garments or other projects.

**Sewing Speed: Moderate to slow.**

**Fabrics Used:**

Lightweight woven fabrics cut on the bias.

**Stitches used:**

Triple Cover Stitch C1-C2-C3

Wide Cover Stitch C1-C3

(This is not a good application for chain or narrow cover stitches)

**Instructions:**

**Stitch Length: 3-4**

**Cutting Blade: Disengaged "LOCKED"**

**Upper Looper: Down**

**Sewing Table: On**

1. Cut bias fabric strips:

3/4 inch Folder - Cut to 7/8 inch wide (22mm)

1-1/2 inch Folder - Cut to 1-5/8 inch wide (37mm)

*Note: The strips must be cut this width even though it is wider than the attachment measurements.*

2. Feed Bias strip, with right side facing up, into the attachment.

3. Pull bias through and up to the needles and under the presser foot.

4. Turn the hand wheel 3-4 times to secure the stitch in the fabric.

5. Align the attachment with the needle position to ensure the folded fabric is caught in the stitching. Make sure the stitch is centered in the belt looping.

6. Be sure to allow 3 inch of extra bias strip at the beginning and ending of project. The extra will be trimmed away when finishing the project.

7. It is best to test sew before attaching the bias to the project.

