



Single Downturn Feller

Available for:
BLETS8, BLETS8AE, BLES8, BLES8W-2, BLE5-3, BLCS

Item No: B0421S10A 1/4 inch (6.5mm)

Item No: B0421S08A 5/8 inch (16mm)

Item No: B0421S09A 1 inch (25mm)

Single Downturn Feller-
1/4 inch

Single Downturn Feller-
5/8 inch

Single Downturn Feller-
1 inch

Stitch Used:
Narrow Left Cover Stitch-
ONLY C1-C2

Stitch Used:
Narrow Left Cover Stitch-C1-C2
Wide Cover Stitch-C1-C3

Stitch Used:
Wide Cover Stitch-C1-C3
Triple Cover Stitch C1-C2-C3
Narrow Left Cover Stitch C1-C2

Application: Hem straight edges of projects.

Fabrics:

1/4 inch Feller - Lt. wt. denim, chambray, cotton broadcloth, calico, polyester, and rayon.

Note: Will not work with polar fleece or sweatshirt fleece.

5/8 inch & 1 inch Feller - Lt.wt. denim, chambray, broadcloth, calico, ultrasuede, leather.

Note: Will work with two layers of lt. wt. polar fleece with no seams.

Sewing Speed: Moderate to slow

INSTRUCTIONS: Stitch Length: 3-4

Cutting Blade: Disengaged "LOCKED"

Upper Looper: Down

Sewing Table: On

Attachment: Make sure the attachment is in the front and the center screw positions of the mounting bracket to avoid being too close to the toe of the presser foot.

1. Secure the attachment to the table with guide fixing screws.
1. To start the hemming, finger press under 1/4 inch for 3-4 inches.
2. Feed the fabric (right side up) through attachment and pull the fabric to the needles and under the presser foot.
3. Make sure the fabric is still folded when placing under the presser foot.
4. Keep fabric turned under when feeding into attachment to insure the fabric will roll under when sewing.

**Note: When you use 1 inch Single Downturn Feller, you had better it is set on more right side and it is fixed by only one screw.*

